


Packing specification

1. Taping & reel form is conforming to JIS C 0806 and EIAJ RC-1009B and a unit in quantity per reel shall be 1,000pcs, 2,000pcs or 3,000pcs.
2. A "Label" on which necessary information is clearly written is on the surface of the packing box and the reel.
3. Goods will be ship out after packing some taping reels into the shipping box.


Taping dimensions

(Conforming to JIS C 0806 TB1208NEIAJ and RC-1009B TE1208N)



Reel dimensions

(Conforming to JIS C 0806 R12R and EIAJ RC-1009B R15)



Model	Region													
	Quantity pcs/reel	a	b	c	d (Φ)	e	f	g	h	j	k	l	m (Φ)	n (Φ)
CMR200T	2,000	16.0	7.5	8.0	-	9.4	0.3	2.15	-	5.0	-	17.5	330	100
CMJ206T	3,000	16.0	9.2	8.0	-	9.5	0.3	2.1	-	3.0	5°	17.5	330	100
CM200C	3,000	16.0	7.5	8.0	1.0	8.2	0.3	2.65	5°	4.0	5°	17.5	330	100
CM250C	3,000	16.0	7.5	8.0	1.0	8.2	0.3	2.65	5°	4.0	5°	17.5	330	100
CM130	3,000	16.0	7.5	4.0	1.0	7.2	0.3	1.4	5°	1.55	5°	17.0	180	50
CM519	3,000	12.0	5.5	4.0	1.0	5.3	0.3	1.1	5°	2.1	5°	13.0	180	60
CM415	3,000	12.0	5.5	4.0	1.0	4.5	0.3	1.0	5°	1.9	5°	13.0	180	60
CM315D	3,000	12.0	5.5	4.0	1.0	3.6	0.3	1.0	5°	1.9	5°	13.0	180	60
CM315DL	3,000	12.0	5.5	4.0	1.0	3.6	0.3	1.0	5°	1.9	5°	13.0	180	60
CM2012H	3,000	8.0	3.5	4.0	1.0	7.2	0.3	1.4	5°	1.55	5°	17.0	180	50
HCM49	1,000	24.0	11.5	12.0	2.0	16.1	0.4	4.3	5°	5.1	5°	25.5	330	100
CM309E	1,000	24.0	11.5	12.0	1.5	11.9	0.4	4.0	5°	4.9	5°	25.5	330	100
CS325S	3,000	8.0	3.5	4.0	1.1	3.5	0.25	0.75	5°	2.8	-	11.4	180	60
CSX-750F	2,000	16.0	7.5	8.0	1.5	7.4	0.3	1.9	5°	5.4	5°	17.5	254	100
SSX-750P	2,000	16.0	7.5	8.0	1.55	7.4	0.3	2.0	5°	5.4	5°	17.5	254	100
CSX-750V	2,000	16.0	7.5	8.0	1.5	7.4	0.3	1.9	5°	5.4	5°	17.5	254	100
CSX-252F	3,000	8.0	3.5	4.0	1.1	2.7	0.25	1.15	5°	2.25	5°	9.0	180	60

CITIZEN